## **VULCAN®** S









P	N	V	V	FI	R
	u	$\mathbf{A}^{\prime}$	٧ı	LI	М

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

**Displacement** 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

Maximum

Torque

46.3 lb-ft @ 6,600 rpm

Fuel System DFI® with 38mm throttle bodies (2), with sub-

throttle valves

Ignition TCBI with Electronic Advance

10.8:1

**Transmission** 6-speed with positive neutral finder

Final Drive Sealed chain

**Electronic Rider** Economical Riding Indicator, Anti-lock Brake

Aids System (ABS)

## **PERFORMANCE**

Front 41mm teles Suspension / Wheel Travel

41mm telescopic fork/5.1 in

Rear Suspension / Wheel Travel

Lay-down offset rear shock with linkage and

adjustable preload/3.2 in

Front Tire 120/70-18

**Rear Tire** 160/60-17

Front Brakes Single 300mm disc with twin-piston caliper

(and ABS)

**Rear Brakes** Single 250mm disc with single-piston caliper

(and ABS)

## **DETAILS**

Frame Type High-tensile steel diamond frame

Rake/Trail 31°/4.7 in

Overall Length 90.9 in

Overall Width 34.6 in

Overall Height 43.3 in

Ground 5.1 in

Clearance Seat Height

27.8 in

**Curb Weight** 498.3 lb\* (ABS), 491.7 lb\* (non-ABS)

Fuel Capacity 3.7 gal

Wheelbase 62.0 in

**Special Features ERGO-FIT®** 

**Color Choices** Metallic Matte Graphite Gray/Metallic Matte

Carbon Gray, Metallic Flat Spark Black

**Warranty** 12 Month Limited Warranty



