
Z500 SE ABS









D	N	V	V	С	D
Г	'U	V	V	C	Λ

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

70.0 x 58.6mm

Bore x Stroke
Compression

Ratio

11.3:1

Maximum Horsepower 51.0 hp¹ @ 10,000 rpm

Maximum Torque

31.7 lb-ft @ 7,500 rpm

Fuel System

DFI® with dual 32mm throttle bodies

Ignition

TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

Electronic Rider

Economical Riding Indicator, Anti-lock Brake

Horizontal back-link with adjustable spring

Aids

System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel 41mm hydraulic telescopic fork/4.7 in

Rear Suspension / Wheel Travel

110/70-17

Front Tire
Rear Tire

150/60-17

preload/5.1 in

Front Brakes Single 310mm semi-floating disc with 2-piston

calipers and ABS

Rear Brakes Single 220mm disc with single-piston caliper and

ABS

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 24.5°/3.6 in

Overall Length 78.5 in

Overall Width 31.5 in

Overall Height 43.3 in

Ground Clearance 5.7 in

Seat Height 30.9 in

Estimated Dry

Weight

339.6 lb** / 341.8 lb** 50-State Model

Curb Weight 370.4 lb* / 372.6 lb* 50-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features ERGO-FIT®, All-LED lighting, Full-color TFT

Instrumentation with Smartphone Connectivity via

RIDEOLOGY THE APP, USB-C outlet

Color Choices Candy Persimmon Red/Metallic Flat Spark Black/

Metallic Matte Graphenesteel Gray

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit mexico.kawasaki-la.com for full product details.