Z900 SE ABS









POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression Ratio 11.8:1

Maximum 123.0 hp¹ @ 9,500 rpm

Horsepower

Maximum Torque 73.1 lb-ft @ 7,700 rpm

Fuel System DFI® with 36mm throttle bodies

Ignition TCBI with Electronic Advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider Aids Economical Riding Indicator, Electronic Cruise Control,

Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-

Enhanced Chassis Orientation Awareness

PERFORMANCE

Front Suspension / Wheel Travel

41mm inverted telescopic fork with compression and rebound damping and spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel Horizontal back-link, Öhlins S46 gas-charged rear shock with rebound damping and spring preload

adjustability/5.5 in

Front Tire 120/70-17

Rear Tire 180/55-17

Front Brakes Dual 300mm semi-floating discs with radial-mount 4-

piston Brembo M4.32 monobloc calipers and ABS

Rear Brakes Single 250mm disc with single-piston caliper and ABS

DETAILS

Frame Type Trellis, high tensile steel

Rake/Trail 24.7°/4.3 in

Overall Length 81.3 in

Overall Width 32.7 in

Overall Height 44.7 in

Ground Clearance 5.7 in

Seat Height 31.9 in

Estimated Dry 427.8 lb** 50-State Model; 425.6 lb** 49-State Model

Weight

Curb Weight

eight

Fuel Capacity 4.5 gal

Wheelbase 57.1 in

Special Features 5" All-digital TFT color instrumentation, All-LED lighting,

USB Type-C outlet, ERGO-FIT®, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDEOLOGY THE APP MOTORCYCLE***

471.9 lb* 50-State Model; 469.7 lb* 49-State Model

Color Choices Metallic Matte Graphenesteel Gray/Metallic Matte Carbon

Gray

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

***RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit mexico.kawasaki-la.com for full product details.