2026 **KLX**®**110R**









3.00 x 12

POWER

Engine 4-stroke, single-cylinder, SOHC, air-cooled

Displacement 112cc

Bore x Stroke 53.0 x 50.6mm

Compression

Ratio

9.5:1

Fuel System Keihin PB18 carburetor and screw type

throttle limiter on grip housing

Ignition DC-CDI

Transmission 4-speed, return shift, automatic centrifugal

and wet, multi-disc clutch

Final Drive Chain

Front Brakes

90mm mechanical drum, cable actuated

Rear Brakes

Rear Tire

110mm mechanical drum, rod actuated

PERFORMANCE

Front 30mm hydraulic telescopic fork/4.3 in Suspension /

Rear Suspension / Wheel Travel

Wheel Travel

Swingarm with single hydraulic shock/4.3 in

Front Tire

2.50 x 14

DETAILS

Frame Type Backbone frame, high-tensile steel

Rake/Trail 24.8°/2.0 in

Overall Length 61.4 in

Overall Width 25.6 in

Overall Height 37.6 in

Ground 8.5 in Clearance

Seat Height 26.8 in

Estimated Dry 158.7 lb**

Weight

Curb Weight 167.5 lb*

Fuel Capacity 1.0 gal

Wheelbase 42.3 in

Color Choices Lime Green, Bright White

Warranty 6 Month Limited Warranty



