







PO	W	ER	
----	---	----	--

Engine 4-stroke, single-cylinder, DOHC, liquid-cooled

Displacement 249cc

Bore x Stroke 78.0 x 52.2mm

Compression

Ratio

14.0:1

Fuel System DFI® with 44mm Keihin throttle body and dual

injectors

Ignition Digital CDI with handlebar-controlled power

modes

Transmission 5-speed, return shift, with wet multi-disc

manual clutch and hydraulic clutch actuation

Final Drive Chain

Electronic Rider

Aids

Power Modes, Kawasaki TRaction Control

(KTRC), Launch Control Mode

PERFORMANCE

Front
Suspension /
Wheel Travel

49mm Showa inverted telescopic coil-spring fork with 16-way compression and rebound damping /12.0 in

damping / izio

Rear Suspension / Wheel Travel

Uni-Trak® with dual-range (4 turns high speed/19-way low-speed) compression damping, 22-way rebound damping and

adjustable preload/12.1 in

Front Tire 80/100-21

Rear Tire 110/100-18

Front Brakes Single semi-floating 270mm Braking petal disc

with dual-piston caliper

Rear Brakes Single 240mm Braking petal disc with single-

piston caliper

DETAILS

Frame Type Aluminum perimeter

Rake/Trail 27.8°/4.8 in

Overall Length 85.8 in

Overall Width 32.3 in

Overall Height 49.6 in

Ground 13.0 in

Clearance

Seat Height 37.2 in

Curb Weight 233.3 lb* without fuel / 243.2 lb*

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

Special Features Smartphone Connectivity via RIDEOLOGY THE

APP KX™, ERGO-FIT®

Color Choices Lime Green

Warranty Not Available

Scan with camera to view videos, key features and more.

