



2026

MULE PRO-DX™ EPS



-  TIMBERLINE GREEN
-  SUPER BLACK



| POWER | | Rear Brakes | |
|---------------------------------|---|------------------------------|---|
| Engine | 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel | Ground Clearance | Dual disc, 1-piston caliper |
| Displacement | 993cc | Fuel Capacity | 10.4 in |
| Maximum Horsepower | 24.0 hp ¹ @ 3,600 rpm | Turning Radius | 7.9 gal |
| Maximum Torque | 38.3 lb-ft @ 2,400 rpm | Cargo Bed Dimensions (LxWxH) | 16.0 ft |
| Bore x Stroke | 74.0 x 77.0mm | Cargo Bed Load Capacity | 54.1 x 53.7 x 11.0 in |
| Compression Ratio | 23.5:1 | Payload Capacity | 999 lb |
| Fuel System | Bosch in-line injection pump | Seating Capacity | 1,574 lb |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) | Towing Capacity | 3-person |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Lighting | 2,000 lb |
| Engine Braking | Yes | DETAILS | |
| Alternator Output (max) | 55 amp | | |
| CAPABILITY | | Overall Length | 133.3 in |
| Front Suspension / Wheel Travel | Double wishbone/8.7 in | Overall Width | 64.0 in |
| Rear Suspension / Wheel Travel | Double wishbone/8.5 in (L)/8.7 in (R) | Overall Height | 77.4 in |
| Front Tires | 26 x 9-12 | Estimated Dry Weight | 1,799.3 lb** |
| Rear Tires | 26 x 11-12 | Curb Weight | 1,885.3 lb* |
| Steering | Electric Power Steering (EPS), Tilt steering | Wheelbase | 92.3 in |
| Park Brake Type | Independent, mechanical disc | Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps |
| Front Brakes | Dual disc, 2-piston caliper | Color Choices | Timberline Green, Super Black |
| | | Warranty | Kawasaki STRONG 3-Year Limited Warranty |

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit mexico.kawasaki-la.com for full product details.