MULE PRO-DX™ EPS









POWER

4-stroke, 3-cylinder, OHV, liquid-cooled, diesel **Engine**

993cc Displacement

Maximum Horsepower 24.0 hp1 @ 3,600 rpm **Maximum Torque** 38.3 lb-ft @ 2,400 rpm

74.0 x 77.0mm Bore x Stroke

Compression Ratio 23.5:1

Bosch in-line injection pump **Fuel System**

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Selectable 2WD/4WD, shaft. Dual mode rear differential with **Final Drive**

differential lock

Engine Braking Yes

Alternator Output 55 amp

(max)

Rear Brakes Dual disc, 1-piston caliper

Ground Clearance 10.4 in **Fuel Capacity** 7.9 gal

Turning Radius 16.0 ft

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

999 lb

Capacity

1,574 lb

54.1 x 53.7 x 11.0 in

Payload Capacity Seating Capacity 3-person

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / Double wishbone/8.7 in Wheel Travel

Rear Suspension / Wheel Travel

26 x 9-12

Front Tires

26 x 11-12

Rear Tires Steering

Electric Power Steering (EPS), Tilt steering

Double wishbone/8.5 in (L)/8.7 in (R)

Park Brake Type

Independent, mechanical disc

Front Brakes

Dual disc, 2-piston caliper

DETAILS

Overall Length 133.3 in **Overall Width** 64.0 in **Overall Height** 77.4 in **Estimated Dry Weight** 1,799.3 lb** **Curb Weight** 1,885.3 lb*

Wheelbase

Warranty

Instruments

Multi-function display includes digital speedometer, fuel

92.3 in

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators,

seatbelt reminder lamps

Color Choices

Timberline Green, Super Black

Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471 KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit mexico.kawasaki-la.com for full product details.