

2026

NINJA[®] ZX[™]-4RR ABS

Kawasaki

Let the Good Times Roll[®]



- LIME GREEN
- METALLIC MATTE GRAPHENESTEEL GRAY/
METALLIC SPARK BLACK
- PEARL ROBOTIC WHITE/METALLIC SPARK BLACK



POWER		Rear Tire	160/60-17
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Front Brakes	Dual 290mm semi-floating discs with radial-mount 4-piston monobloc caliper and ABS
Displacement	399cc	Rear Brakes	Single 220mm disc with single-piston caliper and ABS
Bore x Stroke	57.0 x 39.1mm	DETAILS	
Compression Ratio	12.3:1	Frame Type	Trellis, high-tensile steel
Maximum Horsepower	56.0 hp ¹ @ 11,500 rpm	Rake/Trail	23.5°/3.8 in
Maximum Torque	26.5 lb-ft @ 11,000 rpm	Overall Length	78.3 in
Fuel System	DFI [®] with 34mm throttle valves (4)	Overall Width	30.1 in
Ignition	TCBI with Digital Advance	Overall Height	43.7 in
Transmission	6-speed, return shift	Ground Clearance	5.3 in
Final Drive	Chain	Seat Height	31.5 in
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Power Modes, Anti-lock Brake System (ABS)	Estimated Dry Weight	383.7 lb ^{**}
PERFORMANCE		Curb Weight	414.5 lb [*]
Front Suspension / Wheel Travel	37mm inverted Showa fork with SFF-BP internals and spring preload adjustability/4.7 in	Fuel Capacity	4.0 gal
Rear Suspension / Wheel Travel	Horizontal back-link, Showa BFRC lite gas-charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in	Wheelbase	54.3 in
Front Tire	120/70-17	Special Features	4.3" Full-color TFT Instrumentation, Smartphone Connectivity via RIDEOLGY THE APP
		Color Choices	Lime Green, Metallic Matte Graphenesteel Gray/ Metallic Spark Black, Pearl Robotic White/Metallic Spark Black
		Warranty	12 Month Limited Warranty

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit mexico.kawasaki-la.com for full product details.