NINJA H2® SX SE ABS









POTENCIA

Motor

Cilindrada

Diámetro por carrera

Relación de

compresión

Par motor máximo

Potencia máxima

Sistema de combustible

Encendido

Transmisión

Transmisión final

Asistencia electrónica para el piloto

4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled

998cc

11.2:1

76.0 x 55.0mm

207.0 hp1 @ 10,000 rpm

101.0 lb-ft @ 8,500 rpm

DFI® with 40mm throttle bodies (4); Kawasaki Supercharger

TCBI with Digital Advance

6-speed, return shift, dog-ring

Sealed chain

Economical Riding Indicator, Advanced Rider Assistance Systems (ARAS): Forward Collision Warning (FCW), Blind-Spot Detection (BSD), Adaptive Cruise Control (ACC). Vehicle Hold Assist (VHA), Kawasaki Electronic Control Suspension with Showa Skyhook Technology (KECS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (dual direction), IMU-Enhanced Chassis Orientation Awareness

RENDIMIENTO

Suspensión delantera/recorrido del neumático

Suspensión trasera/ recorrido del

43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/4.7 in

Uni-Trak®, Showa BFRC lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.5 inspring/5.3 in

Neumático delantero 120/70-17 Neumático trasero 190/55-17

Frenos delanteros Dual 320mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo Stylema® calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Frenos traseros Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

DETALLES

Avance

Tipo de chasis	Trellis, high-tensile steel, with swingarm mounting plate
Ángulo de dirección/	24.7° / 4.1 in

Largo total 85.6 in Ancho total 31.1 in

Altura del asiento 49.6 in

Distancia al suelo 5.1 in

Altura del asiento 32.9 in Peso seco estimado 546.8 lb**

590.9 lb* Peso en orden de marcha

Depósito de 5.0 gal combustible

Distancia entre ejes 58.3 in

Características especiales

Supercharged engine, 6.5" Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), Highly Durable Paint, Grip heaters, Tire Pressure Monitoring System (TPMS), Smartphone Connectivity via Kawasaki SPIN infotainment app

Metallic Brilliant Golden Black/Metallic Diablo Black

Colores disponibles

Specifications subject to change. Visite mexico.kawasaki-la.com para obtener detalles completos del producto.

Garantía Garantía limitada de 12 meses

Escanear con cámara para ver videos, características clave v más.

neumático



Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. © 2025 Kawasaki Motors Corp., U.S.A.