2027

Z H2 SE ABS

Kawasaki
Let the Good Times Roll®

GRIS METALLIC MATTE GRAPHENESTEEL/
GRIS METALLIC MATTE CARBON

POTENCIA

Motor	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled, supercharged
Cilindrada	998cc
Diámetro por carrera	76.0 x 55.0mm
Relación de compresión	11.2:1
Potencia máxima	197.0 hp[1] @ 10,500 rpm
Par motor máximo	101.0 lb-ft @ 8,500 rpm
Sistema de combustible	DFI® with 40mm throttle bodies; Kawasaki Supercharger
Encendido	TCBI with Digital Advance
Transmisión	6-speed, return shift, dog-ring
Transmisión final	Sealed chain
Asistencia electrónica para el piloto	Economical Riding Indicator, Kawasaki Electronic Control Suspension (KECS) with Showa Skyhook Technology, Kawasaki Cornering Management Function (KCMF), Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki TRaction Control (KTRC), Kawasaki Engine Brake Control (KEBC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Kawasaki Quick Shifter (KQS) (upshift & downshift), Electronic Cruise Control, IMU-Enhanced Chassis Orientation Awareness

RENDIMIENTO

Suspensión delantera/recorrido del neumático	43mm Showa SFF-BP inverted fork with KECS-controlled rebound and compression damping, manual spring preload adjustability/4.7 in
Suspensión trasera/recorrido del neumático	Uni-Trak®, Showa gas-charged shock with KECS-controlled compression and rebound damping, manual spring preload adjustability/5.3 in
Neumático delantero	120/70-17
Neumático trasero	190/55-17
Frenos delanteros	Dual 320mm discs with radial-mount Brembo M4.32 calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Frenos traseros	Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

DETALLES

Tipo de chasis	Trellis, high tensile steel
Ángulo de dirección/Avance	24.9°/4.1in
Largo total	82.1 in
Ancho total	31.9 in
Altura del asiento	44.5 in
Distancia al suelo	5.5 in
Altura del asiento	32.7 in
Peso seco estimado	487.3 lb**
Peso en orden de marcha	531.4 lb*
Depósito de combustible	5.0 gal
Distancia entre ejes	57.3 in
Características especiales	Supercharged engine, All-digital TFT color Instrumentation, All-LED lighting, Smartphone Connectivity via RIDEOLOGY THE APP MOTORCYCLE
Colores disponibles	Metallic Matte Graphenesteel Gray/Metallic Matte Carbon Gray
Garantía	Garantía limitada de 12 meses

Escanear con cámara para ver videos, características clave y más.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
***RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visite Kawasaki.com.mx para obtener detalles completos del producto.